


TOPSOLAR[®] PV H1Z2Z2-K

TÜV solar PV cable.

BASED ON: EN 50618 / IEC 62930 / UTE C 32-502

DESIGN



Conductor

Class 5 (flexible) tinned copper, based on EN 60228 and IEC 60228.

Insulation

Low smoke zero halogen (LSZH) cross linked rubber insulation.

Outer sheath

Low smoke zero halogen (LSZH) cross linked rubber outer sheath, red or black colour.

APPLICATIONS

The Topsolar[®] PV H1Z2Z2-K cable, which is TÜV certified according to IEC 62930 and EN 50618, is suitable for both fixed and mobile solar installations (solar farms, rooftop solar installations and floating plants).

It is a highly flexible cable compatible with all major connectors and specially designed for the connection of photovoltaic panels. This versatile single-conductor cable is designed to meet the varying needs of the solar industry. Suitable for wet, damp and humid locations.

- Solar PV installations - string cable.

PV WIRE ALSO
AVAILABLE



More information at: www.topcable.com

TOP CABLE TOPSOLAR PV H1Z2Z2-K

FEATURES



Electrical performance

Low voltage 1,5/1,5 1kV (1,8) kV DC.
1,0/1,0 kV (U_0/U).



Based on

EN 50618/ IEC 62930 / UTE C 32-502.



Standards and approvals

TÜV / RETIE / CE / RoHS.



CPR (Construction Products Regulation)

C_{ca} -s1b, d2, a1.



Thermal performance

Maximum service temperature: 120°C.
Maximum short-circuit temperature: 250°C (max. 5 s).
Minimum service temperature: -40°C (fixed and protected installations).



Fire performance

Flame non-propagation based on EN 60332-1 and IEC 60332-1-2.
Fire non-propagation based on EN 50399.
Reaction to fire CPR: C_{ca} -s1b, d2, a1, according to EN 50575.
LSZH (Low Smoke Zero Halogen) based on UNE-EN 60754-1 and IEC 60754-1.
Low smoke emission based on EN 61034 and IEC 61034; Light transmittance > 60%.
Low corrosive gases emission based on UNE-EN 60754-2 and IEC 60754-2.



Mechanical performance

Minimum bending radius: x5 cable diameter.
Impact resistance: AG2 Medium severity.



Chemical performance

Chemical & Oil resistance: Excellent.
Grease & mineral oils resistance: Excellent.
UV UV Resistant based on EN 50618.
O₃ Ozone resistant based on EN 50618.




Water performance

Water presence: AD8 submerged.



Other

Meter by meter marking.
Estimated lifetime 25 years based on EN 50618.
 Optional: rodent proof and termite proof.



Installation conditions

Open Air.
Buried.
On conduit.



Packaging

Available in rolls (lengths of 100 m) and reels.

SOLAR CABLES



TOPSOLAR® PV
H1ZZZ2-K



TOPSOLAR® PV
H1ZZZ2-K DUAL



TOPSOLAR® PV
AL 1500 V



TOPSOLAR® PV
AL 2kV PV WIRE



TOPSOLAR[®] PV H1Z2Z2-K

Dimensions & admissible intensities

Cross section (mm ²)	Diame-ter (mm)	Weight (Kg/km)	Open air (A)	Int. on surface (A)	Int. adjoining to surface (A)	Voltage drop (V/A·km)
1 x 1,5	4,6	35	30	29	24	38,2
1 x 2,5	5,0	45	41	39	33	23,0
1 x 4	5,4	60	55	52	44	14,3
1 x 6	6,0	80	70	67	57	9,49
1 x 10	7,0	120	98	93	79	5,46
1 x 16	8,2	180	132	125	107	3,47
1 x 25	10,2	280	176	167	142	2,23
1 x 35	11,5	375	218	207	176	1,58
1 x 50	13,3	525	276	262	221	1,10
1 x 70	15,0	720	347	330	278	0,772
1 x 95	17,0	930	416	395	333	0,585
1 x 120	18,7	1.175	488	464	390	0,457
1 x 150	21,0	1.475	566	538	453	0,368
1 x 185	23,5	1.805	644	612	515	0,301
1 x 240	26,3	2.345	775	736	620	0,228

Maximum current capacity according to IEC 60364-5-52.

For other installation conditions, please refer to correction factors in the appendix to this catalogue.

Top Cable reserves the right to carry out any modification to the data sheets whatsoever without giving previous notice.

For more information please contact sales@topcable.com



EN2020ED001